



DECOTRON® T332

Water-based cleaning fluid determined for maintenance cleaning of flux residues from soldering frames, pallets and masks, parts of reflow ovens and wave soldering machines.

Specially developed for cleaning filter elements of REHM reflow ovens.
Ready-mix, intended for direct use. Effective for all types of solder pastes and flux types.



Recommended areas for use

Recommended cleaning technology

1. Flux from soldering frames

Air-bubbling

2. Cleaning filters, heat exchangers and other parts of reflow ovens and wave soldering machines

Air-bubbling

Process table

Cleaning technology	Cleaning	Rinse	Drying
Air-bubbling	Decotron® T332	DI water	Hot air

Information

- High compatibility with material and components of the cleaned devices
- The fluid is alkaline, rinse with DI water needed
- Specially developed for cleaning of elements of REHM reflow ovens – high efficiency / high compatibility
- Only for use in AirJet® machines because of possible foaming
- No flash point, can be heated to increase the cleaning efficiency
- Suitable for cleaning of flux residues of all types of solder pastes
- Environmentally-friendly – biodegradable
- Tenside-free, no solid residues

Table of physical and chemical properties

Product appearance:	clear liquid
Colour:	colourless / yellowish
Odour:	ether-like
pH value:	11
Concentration of ready-mix:	25 %
VOC content:	23 %
Flash point:	non-flammable
Density at 25 °C:	0,99 kg/l



Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning

Date of issue:
02. 03. 2020

Check SDS prior to use.
Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Decotron® is a registration trademark of DCT Czech s.r.o.



DECOTRON® T332

General information



Packing

25 litres



Transport

UN number: No

Transport hazard class: No



Handling

Wear nitrile gloves while manipulating with cleaning agent.

It is necessary to stir well the can before use.



Storage

Should be stored in closed containers, in ventilated areas

At temperature 5 – 25 °C



Shelf life:

The minimum shelf life for this product is 5 years.

Technical support

For process implementation and setting, optimization and solving of process issues, trial test, contact your DCT specialist at www.dct.cleaning

Product features

RoHS and REACH compliant, biodegradable, does not contain any halogenated compounds.



RoHS
Compliant



REACH
SVHC



BIODEGRADABLE



We are certified as part of a worldwide quality management system by LLOYD'S.

Date of issue:

02. 03. 2020

Check SDS prior to use.

Check material compatibility in case of contact with sensitive materials susceptible to chemical stress.

Decotron® is a registration trademark of DCT Czech s.r.o.